
ATC™ EVERYDAY COLLECTION®



Everyday Cotton Blend Youth Tee

ATC5050Y


Product Features:

- 9.1-oz, 50/50 cotton/polyester
- Compacted yarns to minimize shrinkage
- Comfort Dry fabric blend offers breathability and wicks moisture away from the skin
- **OEKO-TEX® STANDARD 100**

Youth sizes: XS(2-4), S(6-8), M(10-12), L(14-16), XL(18-20)



1 x 1 rib knit collar



Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print Pantone reference



BLACK Black 6C | WHITE No PMS | ASH GREY* Cool Grey 3C | ATHLETIC HEATHER Cool Grey 5C | DARK HEATHER GREY 7540C | TEAM DARK HEATHER 7545C | CHARCOAL Cool Gray 11C | TEAM CHARCOAL 4294C

NAVY 2380C | TEAM NAVY 533C | ROYAL 2133C | TEAM ROYAL 7686C | SAPPHIRE 7705C | AQUATIC BLUE 2389C | LIGHT BLUE 278C | DARK GREEN 5467C

TEAM FOREST GREEN 5605C | KELLY 340C | SAFETY GREEN 809C | TEAM GOLD 1235C | GOLD 137C | SAFETY ORANGE 021C | ORANGE 172C | RED 200C

ATC5050Y - Everyday Cotton Blend Youth Tee



TEAM RED
199C

MAROON
7644C

SANGRIA
205C

PURPLE
7672C

TEAM PURPLE
669C

*98/2 cotton/polyester

Garment Measurements

Size	XS	S	M	L	XL
Chest - Half Measure	14"	16"	17"	18"	19"
Chest - Full Measure	28"	32"	34"	36"	38"
Body Length from HPS	19"	21"	23"	25"	27"
Sleeves Length - CB	11 3/4"	13 3/4"	14 3/4"	15 3/4"	16 3/4"

Finished measurements in inches. Refer to “How to Measure” guide for detailed information on measurements instructions.

Printing Instructions

Due to the nature of fluorescent dyes in Safety colours, special care must be taken throughout the decoration process. Here are some tips to effectively decorate printed fabrics:
- Garment temperature must not exceed 320°F or 160°C. Exceeding this temperature may cause discoloration
- Dryer temperature and belt speeds must be changed accordingly for fluorescent colours. Check the dryer for proper clearance. When placing garments on the belt, carefully lay them as flat as possible to avoid high spots that may touch the inside of the dryer or come closer to heat elements. Garments touching a hot piece of the dryer may result in discoloration.
- If flashing these garments, do not exceed 2-3 seconds and care should be taken to not have the flash cure unit too close to the garment

SCREEN PRINTING:
- Dwell times in the dryer need to be limited to no more than 90 seconds
- Do not exceed recommended dryer temperature
- Check with your ink supplier for more information.

HEAT TRANSFERS:
- Direct heat contact can cause discoloration. Use cover sheet/flexible application sheet to shield upper platen from garment
- Do not exceed recommended temperature
- Check with your heat transfer supplier for more information

A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on performance fabrics.