ATC™ eurospun®



RING SPUN Youth Tee

ATC8000Y

Product Features:

- 6.8-oz, 100% combed and RING SPUN cotton
- Ultra soft 30 single jersey

Youth sizes: XS(2-4), S(6-8), M(10-12), L(14-16), XL(18-20)



1 x 1 rib knit collar





Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print Pantone reference.



BLACK
Black 6C

WHITE
No PMS

DEEP HEATHER**
424C

ATHLETIC GREY*
Cool Grey 4C

TRUE NAVY
303C

TRUE ROYAL
7462C

SAPPHIRE
640C

PURPLE
7671C

WILD RASPBERRY
214C



TRUE RED
199C

ORANGE
7417C

BLACK CAMO
Light Tone 418C, Mid tone 419C & Black 6C

CAMO
7761C, 553C, 7533C & Black 6C

GREY CAMO
Cool Grey 5C, Cool Grey 10C & Black 6C

*95/5 cotton/viscose **65/35 polyester/cotton
Due to the nature of printed fabrics, special care must be taken throughout the decoration process.
Due to the special nature of these vibrant colours (Extreme Pink & Extreme Yellow), please wash according to the wash instructions before wearing to avoid colour transfer.

ATC8000Y - ATC™ Eurospun® RING SPUN Youth Tee

Garment Measurements

Size	XS	S	M	L	XL
Chest - Half Measure	16"	17"	18"	19"	20"
Chest - Full Measure	32"	34"	36"	38"	40"
Body Length from HPS	20 1/2"	22"	23 1/2"	25"	26 1/2"
Sleeves Length - CB	13 1/2"	14 1/2"	15 1/2"	16 1/2"	17 1/2"

Finished measurements in inches. Refer to “How to Measure” guide for detailed information on measurements instructions.

Printing Instructions for Printed Fabrics

Due to the nature of printed fabrics, special care must be taken throughout the decoration process. Here are some tips to effectively decorate our printed products.

SCREEN PRINTING

- Garment dyes may bleed through screen printed inks, especially when printing on top of print that contains red dye. Sublimation will be most noticeable when using white or light colour inks and may take 24-48 hours to occur.
- Use base blocker ink first (grey works best)
- Using low bleed poly ink is recommended
- Do not exceed recommended dryer temperature
- Check with your ink supplier for other tips

HEAT TRANSFERS

- Use of vinyl heat transfer may help minimize sublimation
- Use cover sheet/flexible application sheet to shield upper platen from sublimation dyes
- Do not exceed recommended temperature
- Check with your heat transfer supplier for other tips

A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on printed fabrics.