



Backpack 20-Can Cooler. 18L

CT89132109

Product Features:

- 600D rugged polyester
- Rain Defender® durable water repellent (DWR)
- PFAS free water repellent fabric treatment
- Seam-sealed to prevent ice from leaking as it melts
- Two interior mesh side pockets



Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print Pantone reference



BLACK
Black C



CARHARTT
BROWN
463C

Due to the nature of polyester and water repellent coatings, special care must be taken throughout the decoration process.
Carhartt® products may not be resold without embellishment. Carhartt® products are not permitted to be shipped to or sold outside of Canada.

CT89132109 - Carhartt® Backpack 20-Can Cooler. 18L

Bag Measurements

Dimensions	15" h x 11.5" w x 6.5" l
Volume	Approx. 1,098 cu. in. /18L

Decoration Area

Location	Size
Bottom Front Pocket	6" h x 8" w
Top Panel	3" h x 9" w

Decoration Recommendations

Due to the nature of 100% polyester fabrics and water repellent coatings, special care must be taken throughout the decoration process. Here are some tips to effectively decorate our polyester products.

Garment temperature must not exceed 320°F or 160°C.

Exceeding this temperature will cause the fabric to shrink, become wavy or cause dye migration.

Dryer temperature and belt speeds must be changed accordingly for polyester fabric.

If flashing these garments, do not exceed 1-2 seconds. Anything longer may damage the fabric as stated above.

EMBROIDERY

- For better results, Magnetic or Clamp Frames are recommended for stability and max decoration range
- Heavy weight fabrics may require a larger needle such as 80/12 or 90/14 Sharp Point

SCREEN PRINTING

- These products require the use of poly inks that cure at a lower temperature, as well as grey or black bleed blockers. Please consult your ink supplier for more information.
- Bonding catalysts may be required for water resistant/waterproof coated fabrics.
- Polyester requires a longer cooling time than cotton. Avoid overlap of garments and screen-print/heat transfer until the garments are cooled. Failure to cool the fabric prior to stacking into a printer's fold may cause the fabric and applied ink to stick together.
- For best results, manual press or specialty equipment may be required

HEAT TRANSFERS

- Low-cure adhesive and bleed blockers are required. Please consult with your transfer supplier for temperature and time recommendations specific to 100% polyester.
- Bonding catalysts may be required for water resistant/waterproof coated fabrics.
- For best results when using heat applied consumables to avoid a color or sheen change, it is recommended to use a protective foam application pad.

A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on polyester fabrics.