





Contrast embroidered The North Face® logo on left hem and right back shoulder

Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print pantone reference

BLACK



Black C

NFOA3LHL

Product Features:

- Exterior: 15D 33 g/m²/1.7 oz lyd, 100% nylon with DWR finish
- **Fill:** 11.5 g/ft² PrimaLoft® ThermoBall™ synthetic insulation
- Secure-zip hand pockets
- Stows in left hand pocket
- Drawcord and toggles at hem

Ladies' sizes: S-2XL

Fabric Features/Benefits:







DURABLE WATER REPELLENT:

DWR is applied to the face of the fabric to provide the first line of defense against wet weather.



INSULATED:

Insulation traps hot air for reduced heat loss and increased warmth.



PACKABLE/STOWABLE:

Highly compressible layer for emergency use or travel.



SYNTHETIC:

Designed to replicate the qualities of down, but retain them even when wet.

Due to the nature of nylon, special care must be taken throughout the decoration process

NF0A3LHL - THE NORTH FACE® ThermoBall™ Trekker Ladies' Vest

GARMENT MEASUREMENTS							
Size	S	M	L	XL	2XL		
Chest - Half Measure	18 3/4"	20"	21 1/2"	23 1/4"	25"		
Chest - Full Measure	37 1/2"	40"	43"	46 1/2"	50"		
Body Length from HPS (At Back)	25 3/8"	26"	26 7/8"	27 3/4"	28 5/8"		

Finished measurements in inches. Refer to "How to Measure" guide for detailed information on measurement instructions.

LADIES' General Sizing Guide							
Size	s	M	L	XL	2XL		
Numeric Size	4-6	8-10	12-14	16	18-20		
Bust	35"-36"	37"-38"	39"-41"	42"-44"	45"-47"		
Waist	26"-27"	28"-30"	30"-32"	33"-35"	36"-38"		
Hip	35"-37"	37"-39"	39"-41"	42"-44"	45"-47"		





PRINTING INSTRUCTIONS FOR NYLON FABRICS

Due to the nature of Nylon fabric, special care must be taken throughout the decoration process. Special care must be taken during the decoration process and after.

Here are some tips to effectively decorate these products.

Heat Transfer/Screen Printing:

- Garment temperature must not exceed 310°F or 154°C.
- Use fast fushion/low cure temperature ink to help prevent the need for a higher temperature to cure the ink.
- A test sample run is recommended in all printing processes, especially if you have a large order or if your printer does not specialize in printing on Nylon fabrics.